



**MAHARASHTRA
PLASTIC & INDUSTRIES**

**KOLSITE
SEMI-AUTOMATIC
STRAPPING MACHINE
(HEAVY DUTY)**



KOLSITE Semi-Automatic strapping machine designed to tension, seal and cut 6-15mm PP strapping around carton boxes. Simply load the strapping onto the machine and feed it through the mechanism Place the carton on top of the deck and feed the strap into the strap guide to activate the strapping process. The machine will automatically tension, seal and cut the strapping, giving a perfect strap every time.

► **It comes along with Trip Arm Assembly Type and Metallic Dispenser**

| SPECIFICATION | |
|--------------------|--|
| Power Supply | 100, 110, 220, 230, 240V., 50/60HZ., 1-Phase |
| Packing Speed | 2.5 sec/strap |
| Max. Tension Force | 10-450N (Adjustable) |
| Strap Size | 6mm-15mm |
| Machine Dimension | 900mm(L) x 580mm(W) x 750mm (H) |
| Machine Weight | 100kg |
| Power Consumption | 0.4KW |



StrapPack

SEMI-AUTOMATIC STRAPPING MACHINE

StraPack-Japan designs this Machine especially for Indian Market. The innovative iQ-400 is amazingly quiet (57.2 dB), which makes it ideal for use in any industrial and commercial facilities. Minimal moving parts and simple sealing head design, assure ease of maintenance and lower cost of operation. Having lower energy consumption than any other strapping machine, it is the new generation of the semi automatic strapping machines.



MODEL: iQ 400

FEATURES AND BENEFITS

- ◆ **Durable Aluminum Structure for Long Life.**
- ◆ **Durable Electrical Equipments specially designed in view of Indian weather condition.**
- ◆ **Excellent Performance even in smaller size like 5-6 mm.**
- ◆ **Lowest Electricity Consumption due to Servo motor and DC current operation.**
- ◆ **Except Heater, entire electrical device operate with 24 V DC Only**
- ◆ **Unique Features in Switching TENSION MODE (Torque/Stroke):**
For Packages of the same size and different hardness, tension is different.
For Packages of the same hardness and different sizes, the tension is different.
- ◆ **Maintenance free Compact strapping Head with Servo motor and operational Friendly Machine**

SPECIFICATION

| | |
|---|--|
| Power supply | 200 - 240V, 50/60 Hz, 1-Phase |
| Packing speed | 1 sec/strap |
| Tension: Torque Mode/Stroke Mode | Up to 450 N (45.9 KGF) 150 mm |
| Strap Size | 5 mm - 15.5 mm |
| Strap Thickness | 0.4 mm - 0.7 mm |
| Min. Package Size | 100mm(W) x 30mm(H) (3-7-8" W x 1-1/8" H) |
| Core Size | 200 ID x 200mm(W) (8"x8") |
| Machine dimension | 780mm(L) x 540mm(W) x 777mm(H) |
| Machine Weight | Approx. 56 KG |
| Power consumption | 0.35 kW |